

DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011

Körapur 030

No. 0109

1. Unique identification code of the product-type:

EN 15651-1: F-EXT-INT 25HM
EN 15651-4: PW-EXT-INT 25 HM

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sealant for facade for interior and exterior application
Sealant for pedestrian walkways interior and exterior application

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Kömmerling Chemische Fabrik GmbH
Zweibrücker Str. 200
66954 Pirmasens

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
System 3 for the reaction to fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body SKZ Tecona GmbH, identification number 1213, performed the determination of the product-type on the basis of type testing under system 3 and issued the test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance

Conditioning: Method B

Substrate: Aluminium with Primer Körabond HG 81

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1:2012 EN 15651-4:2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Elastic recovery	≥ 70 %	
Tensile properties: Secant modulus at 23°C	> 0.4	
Tensile properties: Secant modulus at -20°C	> 0.6	
Tensile properties at maintained extension	NF	
Adhesion/cohesion at variable temperatures	NF	
Adhesion/cohesion at maintained extension after water immersion	NF	
Adhesion/cohesion properties after exposure to heat, salt water and artificial light	NF	
Tear resistance	≤ 12 mm	
Durability	pass	

NF: No Failure

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Knut Göke
 Head of Product Management



Pirmasens, 17.01.2016